



Big Top—Model BTG Assembly

Congratulations! You now own one of the world's best bird feeders! Built of quality materials, it will give you years of enjoyment. Please follow these assembly instructions:

The brass rod has an O-ring on it for shipment. Before proceeding, remove the O-ring from the Long Rod. Place the Collar and Set Screw 1/3 of the way down the Long Rod and tighten Set Screw. Insert or screw the Long Rod up through the hole in the Dome. Slide the Rain Guard down the Long Rod, allowing it to rest on the Dome. Then position the O-ring snugly against the Rain Guard to prevent rainwater from traveling down the Long Rod into the seed. Screw the Snap Hook onto the top of the Long Rod.

For shipment, the Seed Bowl has been partially assembled with the Short Rod Nut & Acorn Nut screwed onto the bottom of the brass Short Rod. Remove the Short Rod Nut & Acorn Nut, set the Seed Bowl on a flat surface and pull the Short Rod out of the seed bowl assembly. Screw the Short Rod Nut back onto the bottom of the Short Rod as far as it will go and reinsert the Short Rod back down into the Seed Bowl, Seed Valve and Port. Screw the Acorn Nut onto the bottom of the Short Rod, but do not tighten. Adjust the Seed Valve openings by rotating the Seed Bowl and the Port in opposite directions. Tighten the Acorn Nut to secure the Seed Valve size setting, being careful not to over tighten. After hanging the assembled Seed Bowl from the Dome, you can determine if the position of the Dome on the Long Rod needs to be adjusted. To do so, simply loosen the Set Screw on the Collar, slide the Dome and Collar to the desired location, and re-tighten the Set Screw.

Droll Yankees Inc. • drollyankees.com
Customer Service: drollbird@drollyankees.com
(860) 779-8980 or (800) 352-9164

