



SEATTLE RAIN GUARD INSTALLATION

Your Seattle Rain Guard is designed for use with a tubular bird feeder, no larger than 2 ½" in diameter.

Attaching to a feeder with a removable cap, such as Droll Yankees New Generation® 15" feeder

1. Remove the top cap by sliding the cap up and pulling the bail wire (handle) out of the bail rod.
2. Squeeze the tube slightly so that you can remove the bail rod out of the tube.
3. Squeeze the ends of the spring clamp to increase its diameter, and slide it into the desired position on the tube.
4. Slide the Seattle Rain Guard onto the tube to rest on top of the spring clamp.
5. Install the bail rod and attach the cap.

Attaching to a feeder with a fixed cap, such as the Droll Yankees A-6

1. Remove the top cap by cutting off or straightening the bent ends of the bail wire (handle) and pulling the wire up through the bail rod and the cap.
2. Remove the bail rod.
3. Squeeze the ends of the spring clamp to increase its diameter, and slide it into the desired position on the tube.
4. Slide the Seattle Rain Guard onto the tube to rest on top of the spring clamp.
5. Install the bail rod.
6. Slide the bail wire through the holes in the cap and then through the bail rod.
7. Using pliers, bend the ends of the bail wire to 90° angles.

Droll Yankees Inc. • drollyankees.com
Customer Service: drollbird@drollyankees.com
(860) 779-8980 or (800) 352-9164