



The New Generation Peanut Feeder with perch rod

For easy filling, slide the metal cap evenly up the bail wire and it will fall to the side.

All Droll Yankees Feeders can be disassembled for easy cleaning or replacing parts.

Cleaning: Please for the sake of the birds, keep your feeders clean! Dirty feeders can harm the birds. Use a mild soap and water solution and a soft bristle brush for thorough and simple cleaning. Dry completely before filling with peanuts.

Disassemble

1. Remove the top cap by sliding the cap up the bail wire and gently pull each end of the bail wire out of the bail rod.
2. Squeeze the wire cage, slightly oblong in shape, horizontal with the bail rod, and reach inside the wire cage and remove the bail rod.
3. To remove the base, place the feeder in a horizontal position. Push downward onto the perch rod against a solid surface such as a table or workbench allowing the perch rod to push up through on the opposite side and remove.

Assemble

1. Install the bail rod by squeezing the wire cage, slightly oblong in shape, inserting the bail rod in the 5th square from the top on each side of the wire cage. Squeeze wire cage back into circular shape.
2. Place bottom of wire cage on base, aligning the squares on the wire cage with the holes in the base.
3. Slide the perch rod into the hole on the base, and push it through until the groove in the perch rod reaches the wire cage.

Note: The groove in the perch rod does not go through first.

4. Using needle nose pliers, squeeze the wires tightly around perch rod.
5. Replace cap by inserting each end of the bail wire into the bail rod and slide cap down into place on the wire cage.

**drollyankees.com • Customer Service: drollbird@drollyankees.com
(860) 779-8980 or (800) 352-9164**

8/06/15

The New Generation Peanut Feeder w/perch rod Instructions 0815

