



Classic TH-3 Thistle Seed Feeder

For easy filling, slide the metal cap evenly up the bail wire and it will fall to the side.

Cleaning: Please for the sake of the birds, keep your feeders clean! Dirty feeders can harm the birds. Use a mild soap and water solution and a soft bristle brush for thorough and simple cleaning. Dry completely before filling with seed.

Disassemble

1. Remove the top cap by cutting off or straightening with pliers, the ends of the bail wire. Pull bail rod out from the side of tube.
2. With feeder in a horizontal position, push downward against each perch rod on a flat surface until it is pushed through to the opposite side and remove. Removing the perch rod located 2nd one up from bottom will release the baffle.
3. To remove the base, unscrew the 2 Phillips screws on each side of the base.
4. Disassemble the TH-A strips (armor bands) by removing the nut and Phillips screw from each TH-A strip or sliding the TH clip off where the two ends are joined on the TH-A strip. This process is easily completed by using a TH clip tool which holds the ends together for you. The TH clip tool can be ordered by calling Droll Yankees.

Assemble

1. Install the TH-A strip (armor band) on the tube by wrapping the TH-A strip around the top pair of ports which are shaped like tear drops. The ports should be centered in both ½" holes on the TH-A strip. While holding both ends of the TH-A strip together with fingertips or with the TH clip tool, replace the Phillips screw and nut or the TH clip. Continue until all TH-A strips are installed on tube.
2. Place baffle inside tube, with the open end facing down, and slide baffle upward, aligning the holes in top of baffle with the round holes underneath the 2nd TH-A strip from the bottom.
3. Perch Rod Installation: **Note: For easier insertion, place perch rods in freezer for 20-30 minutes.**
 - a. Hold a perch rod in an upright position on a carpeted area or workbench. With the feeder in a horizontal position, line up the perch rod with the perch rod hole in the tube. Push the feeder down onto the perch rod, allowing the rod to push up through the tube.
 - b. Align the partially inserted rod with the exit hole and push until the rod extends equally on both sides of the tube.
4. Place base on feeder and install both Phillips screws.
5. Insert bail rod in holes at top of tube. Place top cap on feeder and insert bail wire through the holes in the cap and bail rod. Use pliers to bend the ends of the bail wire to 90° angles.

drollyankees.com • Customer Service: drollbird@drollyankees.com
(860) 779-8980 or (800) 352-9164

09/11/15

Classic TH-3 Thistle Feeder Instructions 0915

