

## Onyx Clever Clean® Sunflower & Nyjer Feeder

Droll Yankees feeders can be disassembled for easy cleaning and part replacement.

**Cleaning:** Please for the sake of the birds, keep your feeders clean! Dirty feeders can harm the birds. Use a mild soap & water solution and a soft brush for thorough, simple cleaning. Dry completely before filling with seed.

### Disassemble

1. Remove the top cap by sliding the top cap halfway up the bail wire which will allow the top cap with bail wire to fall to the side. Gently pull each end of the bail wire out of the bail rod.
2. Squeeze the end of the tube, horizontal with the bail rod, until one end of the bail rod releases from the tube and reach inside the tube and remove the bail rod.
3. Remove the base by turning the knob located underneath the bottom of the base counter-clockwise.
4. Disassemble the perch by first removing the onyx button screw using a 7/64" standard or 2 mm hex socket or Allen wrench. Remove the black outer perch by slowly pulling the curved end of the black outer perch towards you. Place your thumb underneath the end of the silver inner perch and push upward until the metal post on the back of the silver inner perch is pulled out of the small hole in the tube. Lift the silver inner perch off the bottom edge of the port hole in the tube.

### Assemble

1. Install the bail rod inside the top of the tube by lining the bail rod up with both of the designated holes. Apply pressure to the outside of the tube at both ends of the bail rod until the tube locks into both grooves in the bail rod.
2. Perch Installation: On the backside of the silver inner perch there is a square metal piece with a hole for the onyx button screw. Lay that section of the silver inner perch horizontally on the bottom edge, inside the tube of the port hole. Push downward on the end of the silver inner perch making certain that the square metal piece with hole for the onyx button screw is positioned **inside**, the bottom edge of the port hole. Continue to push downward until the post on the back of the silver inner perch is pushed through the small hole in the tube. Slide the curved end of the black outer perch under the silver inner perch making certain that the metal tab on the top of the black outer perch is positioned inside the tube. The black outer perch should fit flush against the side of the tube. Replace the onyx button screw using a 7/64" standard or 2mm hex socket or Allen wrench.
3. Install the base on the feeder by inserting the silver metal posts which are located on the back of the two lower silver inner perches, into the slots of the base. Twist the knob underneath the bottom of the base clockwise to secure.
4. Replace the top cap by inserting each end of the bail wire into the bail rod and slide the top cap down into place on the tube.

