



## ***The New Generation® Peanut Feeder with perch rod***

Droll Yankees feeders can be disassembled for easy cleaning and part replacement.

**Cleaning:** Please for the sake of the birds, keep your feeders clean! Dirty feeders can harm the birds. Use a mild soap & water solution and a soft brush for thorough, simple cleaning. Dry completely before filling with peanuts.

### **Disassemble**

1. Remove the top cap by sliding the top cap halfway up the bail wire which will allow the top cap with bail wire to fall to the side. Gently pull each end of the bail wire out of the bail rod.
2. Squeeze the wire cage, slightly oblong in shape, horizontal with the bail rod, and reach inside the wire cage and remove the bail rod.
3. Place the feeder in a horizontal position on a flat surface. Push the base down onto the perch rod, the end without the groove, until the perch rod is flush with the side of the base. Remove the perch rod from the opposite side of the base.

### **Assemble**

Use needle nose pliers to enlarge the squares, and also to bend the wire back tightly around the bail rod and the perch rod.

1. Position the wire cage with the full size squares at the top, and the half size squares at the bottom. Turn the wire cage so that the seam on the wire cage will be positioned at the back of the feeder.
  2. Install the bail rod by squeezing the top of the wire cage, slightly oblong in shape, inserting the bail rod into the 5<sup>th</sup> square from the top on each side of the wire cage. Squeeze the wire cage back into a circular shape.
  3. Place the wire cage on the base. Follow the row at the end of the bail rod down the wire cage to the bottom. Turn the base to align the hole in the base with that square.
  4. Place the feeder in a horizontal position on a flat surface. Push the base down onto the perch rod, the end without the groove, until the groove in the perch rod is flush with the wire cage.
- Note: The groove in the perch rod does not go through first.**
5. Replace the top cap by inserting each end of the bail wire into the bail rod and slide the top cap down into place on the wire cage.

Droll Yankees Inc. • [www.drollyankees.com](http://www.drollyankees.com)  
Customer Service: [drollbird@drollyankees.com](mailto:drollbird@drollyankees.com)  
(860) 779-8980 or (800) 352-9164

CJM13BLP feeder illustrated

