

The Winner® Window Feeder (W-1)

Droll Yankees Feeders can be disassembled for easy cleaning and part replacement.

Cleaning: Please for the sake of the birds, keep your feeders clean! Dirty feeders can harm the birds. Use a mild soap & water solution and a soft brush for thorough, simple cleaning. Dry completely before filling with seed, fruit, mealworms or suet.

Disassemble

1. Remove the feeder from the bar with suction cups and the bumper with suction cup by lifting the feeder gently upward.
2. While holding the brass rod, turn the dome counter-clockwise (viewed from the bottom) for removal of the dome from the brass rod.
3. Turn the thumb screw counter-clockwise and pull the brass rod out of the plastic column of the dish.
4. The bar with suction cups and the bumper with suction cup can be removed from the window by gently lifting the edge of each suction cup.

Assemble

1. Place the threaded end of the brass rod into the metal insert which is located in the center of the dome and turn the dome clockwise (viewed from the bottom) until the dome is secure.
2. Insert the smooth end of the brass rod halfway into the plastic column and position the dome over the dish. Tighten the thumbscrew by turning it clockwise.

Note: The dome can be adjusted by moving the brass rod up or down inside the plastic column to the desired height.

3. Before placing the bumper with suction cup and the bar with suction cups on a clean, dry window, rub a little oil from the side of your nose onto the suction cups.
4. Position and press the bumper with suction cup against the window at the desired height.
5. While the feeder is sitting on a level surface, hold the bar with suction cups on both ends making certain that the arrow in the center of the bar is pointing upward and the writing imprinted on the bar can be read, and position the bar with suction cups centered under the lip on the backside of the dome.
6. While holding the bar with suction cups slightly away from the window, hook the dish gently onto the bumper with suction cup using the lip which is located on the backside of the dish. Position the bar with suction cups, making certain that it is level, and press the bar with suction cups firmly against the window.

